Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-485-3622

## **Electrical Resistance:**

30.100 ohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

#### 275.0

**Inclosure Method:** 

Encased

**Terminal Type:** 

Tab, solder lug

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.100

Terminal Length:

Between 0.376 inches and 0.500 inches

**Body Length:** 

Between 1.000 inches and 1.124 inches

**Body Width:** 

Between 0.469 inches and 0.593 inches

**Body Height:** 

Between 0.531 inches and 0.593 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.709 inches and 0.729 inches

### **Power Dissipation Rating In Watts:**

8.000 free air

**Terminal Width:** 

0.140 inches

**End Application:** 

Control panel

Mounting Hole Size:

Between 0.120 inches and 0.130 inches

Cubic Measure (non-core):

0.317 cubic inches

Unpackaged Unit Weight:

15.0 grams

Style Designator:

Axial terminal (s)

#### **Test Data Document:**

81349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).



## **Specification Data:**

81349-mil-prf-39009/1 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0

# Mil-std (military Standard):

Mil-prf-39009 spec.