## NSN 5905-01-485-3632

**Test Data Document:** 

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-485-3632

**Electrical Resistance:** 30.000 ohms **Resistance Tolerance In Percent:** -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 **Inclosure Method:** Encased **Terminal Type:** Tab, solder lug **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: **Terminal Length:** Between 0.376 inches and 0.500 inches **Body Length:** Between 1.876 inches and 2.000 inches **Body Width:** Between 0.532 inches and 0.656 inches **Body Height:** Between 0.594 inches and 0.656 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.552 inches and 1.572 inches **Power Dissipation Rating In Watts:** 6.000 free air **Terminal Width:** 0.140 inches **End Application:** Control panel **Mounting Hole Size:** Between 0.012 inches and 0.130 inches Cubic Measure (non-core): 0.719 cubic inches **Unpackaged Unit Weight:** 32.0 grams **Style Designator:** Axial terminal (s)

81349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5905-01-485-3632

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Specification Data:
81349-mil-prf-39009/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0

Mil-std (military Standard):

Mil-prf-39009 spec.