Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-485-6356

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

Electrical Resistance:

49.900 ohms

Resistance Tolerance In Percent:

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

Inclosure Method:

Encapsulated

Terminal Quantity:

8

Terminal Type:

Pin

Reliability Indicator:

Not established

Terminal Length:

Between 0.125 inches and 0.150 inches

Body Length:

Between 0.760 inches and 0.798 inches

Body Width:

0.098 inches

Body Height:

Between 0.177 inches and 0.197 inches

Schematic Diagram Designator:

Ladder network

Power Dissipation Rating In Watts:

0.480 total network

End Application:

An/bsy-2 depo

Identical Value Resistor Quantity:

7 each resistor

Style Designator:

Single inline

Test Data Document:

81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-83401/8 government specification

NSN 5905-01-485-6356

Film Fixed Resistor Network - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-83401 spec.