# NSN 5905-01-485-6419

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-485-6419

### Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0/+50.0

#### **Electrical Resistance:**

825.000 ohms

#### **Resistance Tolerance In Percent:**

-0.100/+0.100

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

#### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+175.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

Wire lead

### Mil-std-1276 Wire Lead Type Designator:

С

#### **Reliability Indicator:**

Established

## Reliability Failure Rate Level In Percent:

0.001

#### Terminal Length:

Between 0.984 inches and 1.512 inches

#### **Body Diameter:**

Between 0.050 inches and 0.080 inches

#### **Body Length:**

Between 0.130 inches and 0.170 inches

#### **Power Dissipation Rating In Watts:**

0.050 free air

#### End Application:

An/bsy-2 depo

#### Style Designator:

Axial terminal each end

#### Test Data Document:

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-prf-55182/7 government specification

## Shelf Life:

N/a

### Unit Of Measure:

# NSN 5905-01-485-6419

Film Fixed Resistor - Page 2 of 2

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.

