# NSN 5905-01-485-7593

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-485-7593

### Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-25.0/+25.0

#### **Electrical Resistance:**

162.000 kilohms

#### **Resistance Tolerance In Percent:**

-0.500/+0.500

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

#### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+175.0

#### **Inclosure Method:**

Hermetically sealed

#### **Terminal Type:**

Wire lead

### Reliability Indicator:

Established

## Reliability Failure Rate Level In Percent:

0.010

#### Terminal Length:

Between 1.375 inches and 1.625 inches

#### **Body Diameter:**

Between 0.085 inches and 0.165 inches

#### **Body Length:**

Between 0.260 inches and 0.437 inches

#### **Power Dissipation Rating In Watts:**

0.125 free air

#### **End Application:**

An/bsy-2 depo

#### Style Designator:

Axial terminal each end

#### Test Data Document:

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-prf-55182/3 government specification

#### Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:
- No

# NSN 5905-01-485-7593

Film Fixed Resistor - Page 2 of 2

Fiig: A001a0 Mil-std (military Standard):

Mil-prf-55182 spec.

