## NSN 5905-01-486-4516

**Section Quantity:** 

N/a

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-486-4516

| Body Style:   |
|---|
| Cylindrical bushing mounted                               |
| Reliability Indicator:                                    |
| Not established   |
| Overall Height:   |
| 2.060 inches  |
| Body Diameter:  |
| 2.060 inches  |
| Shaft Diameter:   |
| Between 0.248 inches and 0.250 inches                     |
| Shaft Length:   |
| Between 0.844 inches and 0.906 inches                     |
| Mounting Bushing Length:                                  |
| Between 0.360 inches and 0.390 inches                     |
| Body Length:  |
| Between 0.850 inches and 1.100 inches                     |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Screw Thread Diameter:                                    |
| 0.375 inches  |
| Screw Thread Series Designator:                           |
| Unef  |
| Screw Thready Qty Per Inch (tpi):                         |
| 32.0  |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Standard bushing  |
| Electrical Resistance Per Section:                        |
| 5000.0 ohms single section                                |
| Power Dissipation Rating Per Section In Watts:            |
| 4.0 free air single section                               |
| Resistance Tolerance Per Section In Percent:              |
| -10.0/+10.0 single section                                |
| Terminal Type And Quantity:                               |
| 3 tab, solder lug   |
| Shelf Life:   |
| N/a   |

## NSN 5905-01-486-4516

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| U | n | it | Of | Μe | eas | ur | e: |
|---|---|----|----|----|-----|----|----|
|   |   |    |    |    |     |    |    |

--

Demilitarization:

No

Fiig:

A002a0