Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-488-4437

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

#### **Electrical Resistance:**

1.000 kilohms

## **Resistance Tolerance In Percent:**

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

## **Inclosure Method:**

Encapsulated

#### **Terminal Quantity:**

10

# Terminal Type:

Pin

# Reliability Indicator:

Not established

# Terminal Length:

Between 0.125 inches and 0.150 inches

## **Body Length:**

Between 0.968 inches and 0.998 inches

## **Body Width:**

Between 0.332 inches and 0.352 inches

## **Body Height:**

0.052 inches

## Schematic Diagram Designator:

Ladder network

## **Power Dissipation Rating In Watts:**

1.800 total network

#### **End Application:**

Type 18 adbf

# Identical Value Resistor Quantity:

9 each resistor

#### **Precious Material And Location:**

Internal connections gold

#### Style Designator:

Single inline

#### **Test Data Document:**

81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5905-01-488-4437

Film Fixed Resistor Network - Page 2 of 2



**Specification Data:** 

81349-mil-prf-83401/20 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-83401 spec.