## NSN 5905-01-489-1891

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-489-1891

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -140.0 to 140.0  Electrical Resistance: 620.000 kilohms  Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	
Electrical Resistance: 620.000 kilohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0 to 125.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Not established  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.094 inches and 0.124 inches  Body Length: Between 0.283 inches and 0.343 inches  Power Dissipation Rating In Watts:  0.800 free air  End Application:  Joint strs rd  Precious Material And Location:  Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-65.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	125.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	-65.0 to 125.0
Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.094 inches and 0.124 inches  Body Length: Between 0.283 inches and 0.343 inches  Power Dissipation Rating In Watts: 0.800 free air  End Application: Joint strs rd  Precious Material And Location: Terminal surfaces gold  Style Designator: Axial terminal each end  Shelf Life: N/a  Unit Of Measure: Demilitarization: No	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.124 inches Body Length: Between 0.283 inches and 0.343 inches Power Dissipation Rating In Watts: 0.800 free air End Application: Joint strs rd Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Encapsulated
Reliability Indicator: Not established  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.094 inches and 0.124 inches  Body Length: Between 0.283 inches and 0.343 inches  Power Dissipation Rating In Watts: 0.800 free air  End Application: Joint strs rd  Precious Material And Location: Terminal surfaces gold  Style Designator: Axial terminal each end  Shelf Life: N/a  Unit Of Measure: Demilitarization: No	Terminal Type:
Not established  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.094 inches and 0.124 inches  Body Length: Between 0.283 inches and 0.343 inches  Power Dissipation Rating In Watts: 0.800 free air  End Application:  Joint strs rd  Precious Material And Location:  Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Wire lead
Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.094 inches and 0.124 inches  Body Length: Between 0.283 inches and 0.343 inches  Power Dissipation Rating In Watts: 0.800 free air  End Application:  Joint strs rd  Precious Material And Location:  Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Reliability Indicator:
Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.094 inches and 0.124 inches  Body Length:  Between 0.283 inches and 0.343 inches  Power Dissipation Rating In Watts: 0.800 free air  End Application:  Joint strs rd  Precious Material And Location:  Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Not established
Body Diameter:  Between 0.094 inches and 0.124 inches  Body Length:  Between 0.283 inches and 0.343 inches  Power Dissipation Rating In Watts: 0.800 free air  End Application:  Joint strs rd  Precious Material And Location:  Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Terminal Length:
Between 0.094 inches and 0.124 inches  Body Length: Between 0.283 inches and 0.343 inches  Power Dissipation Rating In Watts: 0.800 free air  End Application:  Joint strs rd  Precious Material And Location:  Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Between 1.375 inches and 1.625 inches
Body Length:  Between 0.283 inches and 0.343 inches  Power Dissipation Rating In Watts:  0.800 free air  End Application:  Joint strs rd  Precious Material And Location:  Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Body Diameter:
Between 0.283 inches and 0.343 inches  Power Dissipation Rating In Watts:  0.800 free air  End Application:  Joint strs rd  Precious Material And Location:  Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Between 0.094 inches and 0.124 inches
Power Dissipation Rating In Watts:  0.800 free air  End Application:  Joint strs rd  Precious Material And Location:  Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Body Length:
0.800 free air  End Application: Joint strs rd  Precious Material And Location: Terminal surfaces gold  Style Designator: Axial terminal each end  Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.283 inches and 0.343 inches
End Application: Joint strs rd  Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Power Dissipation Rating In Watts:
Joint strs rd  Precious Material And Location:  Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	0.800 free air
Precious Material And Location: Terminal surfaces gold Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	End Application:
Terminal surfaces gold  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Joint strs rd
Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Precious Material And Location:
Axial terminal each end  Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal surfaces gold
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Style Designator:
N/a Unit Of Measure: Demilitarization: No	Axial terminal each end
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization:	N/a
No	Unit Of Measure:
No	<del></del>
	Demilitarization:
Fiig:	No
-	Fiig:
A001a0	A001a0