NSN 5905-01-491-0231

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-491-0231

Demilitarization:
Unit Of Measure:
N/a
Shelf Life:
81349-mil-prf-55182/6 government specification
Specification Data:
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Test Data Document: 813/10-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Axial terminal each end Test Pote Posument
Style Designator:
0.500 free air
Power Dissipation Rating In Watts:
Between 0.500 inches and 0.875 inches
Body Length: Return 0.500 inches and 0.875 inches
Between 0.160 inches and 0.328 inches
Body Diameter: Return 0.160 inches and 0.228 inches
Between 1.000 inches and 1.625 inches
Terminal Length:
0.010 Townshell another
Reliability Failure Rate Level In Percent:
Established Reliability Failure Retail avail in Research
Reliability Indicator:
Mil-std-1276 Wire Lead Type Designator:
Wire lead
Terminal Type:
Encapsulated Townsian Towns
Inclosure Method:
-55.0/+175.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
175.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Full Rated Power:
-1.000/+1.000
Resistance Tolerance In Percent:
82.500 kilohms
Electrical Resistance:
-100.0/+100.0
Tempurature Coefficient Of Resistance in Ppm Per Deg Ceisius:

No

NSN 5905-01-491-0231

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.