NSN 5905-01-491-0550

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-491-0550

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.04-50.0 Electrical Resistance: 97.600 kilohms Resistance Tolerance In Percent: -0.100/-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -50.04-175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.000 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating in Wates: 0.500 free air Style Designator: Axial terminal seach end Test Data Document: 814349-mill-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification rewironmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data:	View Online at https://aerobasegroup.com/nsn/5905-01-491-0550
Electrical Resistance: 97.600 kilohms Resistance Tolerance in Percent: -0.100/+0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Length: Between 0.160 inches and 0.328 inches Body Diameter: Between 0.160 inches and 0.875 inches Power Dissipation Rating in Watts: 0.500 free air Style Designator: Akial terminal each end Test Data Document: B1349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: B1349-mil-prf-55182/6 government specification	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -0.100/40-100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mill-sat-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.825 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: B1349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-prf-55182/6 government specification	-50.0/+50.0
Resistance Tolerance in Percent: -0.100/+0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Milli-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.500 inches and 0.328 inches Body Diameter: Between 0.500 inches and 0.375 inches Power Dissipation Rating in Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: B1349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Specification Data: B1349-mil-prf-551826 government specification	Electrical Resistance:
-0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.500 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-551826 government specification	97.600 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 1.000 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-prf-551826 government specification	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average*, "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.825 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Diameter: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Diameter: Between 0.160 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: B1349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-prf-55182/6 government specification	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mili-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: B1349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-prf-55182/6 government specification	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mili-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: B1349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-prf-55182/6 government specification	175.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Diameter: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	-55.0/+175.0
Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Inclosure Method:
Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Encapsulated
Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Terminal Type:
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Wire lead
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Mil-std-1276 Wire Lead Type Designator:
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	C
Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Reliability Indicator:
Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Established
Terminal Length: Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Reliability Failure Rate Level In Percent:
Between 1.000 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	0.010
Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Terminal Length:
Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Between 1.000 inches and 1.625 inches
Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Body Diameter:
Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Between 0.160 inches and 0.328 inches
Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Body Length:
O.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Between 0.500 inches and 0.875 inches
Style Designator: Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	0.500 free air
Test Data Document: 81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Style Designator:
81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-prf-55182/6 government specification	81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-prf-55182/6 government specification	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-prf-55182/6 government specification	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
	Specification Data:
Shelf Life:	81349-mil-prf-55182/6 government specification
	Shelf Life:
N/a	N/a
Unit Of Measure:	Unit Of Measure:

No

Demilitarization:

NSN 5905-01-491-0550

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.