## NSN 5905-01-493-2416

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-493-2416

Electrical Resistance:
220.000 ohms
Resistance Tolerance In Percent:
-1.000/+1.000 Ambient Tempurature In Deg Coleius At Full Peted Bower.
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Inclosure Method:
Encased
Terminal Type: Solder stud
Reliability Indicator:
Established  Reliability Fallors Retail and the Research
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
Between 0.250 inches and 0.374 inches
Body Length:
Between 0.688 inches and 0.812 inches
Body Width:
Between 0.376 inches and 0.500 inches
Body Height:
Between 0.375 inches and 0.437 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 0.552 inches and 0.572 inches
Power Dissipation Rating In Watts:
5.000 free air
Terminal Width:
0.140 inches
End Application:
Control unit
Mounting Hole Size:
Between 0.089 inches and 0.099 inches
Unpackaged Unit Weight:
8.0 grams
Style Designator:
Axial terminal (s)
Supplementary Features:
Weapons system designator is jdn
Test Data Document:

81349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5905-01-493-2416

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Specification Data:
81349-mil-prf-39009/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0

Mil-std (military Standard):

Mil-prf-39009 spec.