NSN 5905-01-493-8691

Section Quantity:

A single section

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-493-8691

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.158 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Switch Type:
Rotary
Actuator Type:
Single shaft
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
50000.0 ohms single section
Power Dissipation Rating Per Section In Watts:
2.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Switch Current Type And Rating In Amps:
2.000 ac and 10.000 dc
Standard Taper Curve Per Section:

NSN 5905-01-493-8691

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0