Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-493-8691

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.158 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.625 inches

Switch Type:

Rotary

Actuator Type:

Single shaft

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

50000.0 ohms single section

Power Dissipation Rating Per Section In Watts:

2.25 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Switch Current Type And Rating In Amps:

2.000 ac and 10.000 dc

Standard Taper Curve Per Section:

A single section



Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0