## NSN 5905-01-494-0635

-100.0/+100.0

13.000 kilohms

-1.000/+1.000

70.0

**Electrical Resistance:** 

**Resistance Tolerance In Percent:** 

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-494-0635

**Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:** 

Ambient Tempurature In Deg Celsius At Full Rated Power:

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
16
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
Between 0.125 inches and 0.150 inches
Body Length:
Between 0.760 inches and 0.876 inches
Body Width:
0.200 inches
Body Height:
Between 0.240 inches and 0.305 inches
Power Dissipation Rating In Watts:
1.600 total network
Identical Value Resistor Quantity:
8 each resistor
Style Designator:
Dual inline
Test Data Document:
81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-83401/2 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>

## NSN 5905-01-494-0635

Film Fixed Resistor Network - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-83401 spec.