## NSN 5905-01-496-1269

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-496-1269 **Electrical Resistance:** 806.000 ohms **Resistance Tolerance In Percent:** -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 **Inclosure Method:** Encapsulated **Terminal Type:** Wire lead **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.010 **Terminal Length:** 1.500 inches **Body Diameter:** Between 0.156 inches and 0.218 inches **Body Length:** Between 0.750 inches and 0.874 inches **Power Dissipation Rating In Watts:** 2.000 free air **Cubic Measure (non-core):** 0.022 cubic inches **Unpackaged Unit Weight:** 0.9 grams Style Designator: Axial terminal each end **Test Data Document:** 81349-mil-prf-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-prf-39007/5 government specification Shelf Life: N/a **Unit Of Measure:** 

A001a0

No Fiig:

**Demilitarization:** 

## NSN 5905-01-496-1269

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-39007 spec.