## NSN 5905-01-498-0505

Hybrid Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-498-0505

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Cylindrical bushing mounted   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 0.250 inches  |
| Body Diameter:  |
| 0.906 inches  |
| Shaft Diameter:   |
| 0.250 inches  |
| Shaft Length:   |
| 0.625 inches  |
| Mounting Bushing Length:  |
| 0.375 inches  |
| Body Length:  |
| 0.453 inches  |
| Shaft Style:  |
| Round   |
| Actuator Type:  |
| Single shaft  |
| Nonturn Device Location:  |
| At 9 oclock   |
| Nonturn Device Radius:  |
| 0.438 inches  |
| Center To Center Distance Between Terminals:                                |
| 0.876 inches  |
| Terminal Location:  |
| Radially positioned over less than half the circumference                   |
| Mounting Method:  |
| Terminal  |
| Electrical Resistance Per Section:  |
| 10000.000 ohms single section   |
| Center To Center Distance Between Center Terminal And Outside Terminal:     |
| 0.438 inches  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |
| 1.0 free air single section   |
| Resistance Tolerance Per Section In Percent:                                |
| -10.000/+10.000 single section  |

## NSN 5905-01-498-0505

Hybrid Variable Resistor - Page 2 of 2



| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |  |
|---|--|
| 70.0 single section   |  |
| Terminal Type And Quantity:   |  |
| 3 pin   |  |
| Shelf Life:   |  |
| N/a   |  |
| Unit Of Measure:  |  |
| <u>.</u>  |  |

No

Demilitarization:

Fiig:

A002a0