Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-498-1079

### **Electrical Resistance:**

3.320 ohms

### **Resistance Tolerance In Percent:**

-1.000 to 1.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

### **Inclosure Method:**

Encapsulated

### **Terminal Type:**

Tab, solder lug

**Reliability Indicator:** 

Not established

#### **Terminal Length:**

Between 0.250 inches and 0.374 inches

### **Body Diameter:**

Between 0.376 inches and 0.500 inches

### **Body Length:**

Between 0.688 inches and 0.812 inches

### **Power Dissipation Rating In Watts:**

6.000 free air

# Err Default:

0.140 inches

#### Style Designator:

Axial terminal each end

### **Test Data Document:**

81349-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-prf-39009/1 government specification

# Shelf Life:

N/a

# Unit Of Measure:

### **Demilitarization:**

No

# Fiig:

A001a0

### Mil-std (military Standard):

Mil-prf-39009 spec.