## NSN 5905-01-498-9312

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-498-9312 **Electrical Resistance:** 0.634 kilohms **Resistance Tolerance In Percent:** -0.100/+0.100Ambient Tempurature In Deg Celsius At Full Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 **Inclosure Method:** Encapsulated **Terminal Type:** Wire lead **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.010 **Terminal Length:** 1.500 inches **Body Diameter:** Between 0.281 inches and 0.343 inches **Body Length:** Between 0.813 inches and 0.937 inches **Power Dissipation Rating In Watts:** 7.000 heat sink **End Application:** Common rack **Unpackaged Unit Weight:** 5.0 grams Style Designator: Axial terminal each end **Test Data Document:** 81349-mil-prf-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-prf-39007/10 government specification Shelf Life: N/a **Unit Of Measure:** 

**Fiig:** A001a0

No

**Demilitarization:** 

## NSN 5905-01-498-9312

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-39007 spec.