## NSN 5905-01-499-6706

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-499-6706 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Terminal Length:** Between 0.120 inches and 0.140 inches **Body Diameter:** Between 0.484 inches and 0.516 inches **Shaft Diameter:** Between 0.122 inches and 0.126 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Center To Center Distance Between Terminals:** 0.200 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 50.0 kilohms single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section

**Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

## NSN 5905-01-499-6706

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0