## NSN 5905-01-500-1569

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-500-1569 **Electrical Resistance:** 1651,000 ohms **Resistance Tolerance In Percent:** -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 **Inclosure Method:** Encapsulated **Terminal Type:** Wire lead **Reactance Characteristic:** Inductive **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** Between 0.065 inches and 0.105 inches **Body Length:** Between 0.219 inches and 0.281 inches **Power Dissipation Rating In Watts:** 1.000 free air **End Application:** Panel, interface dev; e-nsn isil; panel, interface device pccn: p9hl20; cv-22b se; specification gse allow (hv-22b); specification gse allow (mv-22b) **Criticality Code Justification:** Agav **Special Features:** 0.35 grams weight **Unpackaged Unit Weight:** 0.4 grams Style Designator: Axial terminal each end **Specification Data:** 81349 - rwr81s1651fm government specification

N/a

Shelf Life:

**Unit Of Measure:** 

**Specification Or Standard:** 

Mil-prf-39007/9h reference number

## NSN 5905-01-500-1569

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39007 spec.