NSN 5905-01-500-5661

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-500-5661

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
Between 0.300 inches and 0.330 inches
Shaft Diameter:
0.060 inches
Shaft Length:
0.040 inches
Body Length:
Between 0.360 inches and 0.390 inches
Body Width:
0.150 inches
Body Height:
Between 0.360 inches and 0.390 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.100 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
50.0 ohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

1.0 free air single section

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-01-500-5661

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No