NSN 5905-01-501-3187

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-501-3187
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Mounting Bushing Length:
Between 0.300 inches and 0.330 inches
Body Length:
Between 0.980 inches and 1.020 inches
Maximum Starting Torque:
0.60 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.005 inches
Shaft Radial Play:
0.003 inches
Mechanical Backlash In Deg Angular Rotation:
1.0
Terminal Location:
Upper adjacent side two rows
Electrical Resistance Per Section:
100.0 ohms c and better flooring
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Special Features:
Split locking bushing
Precious Material And Location:
Terminals gold
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-01-501-3187

Precision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0