## NSN 5905-01-501-5963

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-501-5963

Tempurature Coefficient	Of Resistance In	Ppm Per Deg Celsius:
-------------------------	------------------	----------------------

-30.0/+30.0

**Electrical Resistance:** 

50.000 ohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.00

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0/+275.0

**Inclosure Method:** 

Encased

**Terminal Type:** 

Tab, solder lug

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.100

**Terminal Length:** 

Between 0.250 inches and 0.374 inches

**Body Length:** 

Between 0.688 inches and 0.812 inches

**Body Width:** 

Between 0.376 inches and 0.500 inches

**Body Height:** 

Between 0.375 inches and 0.437 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 

Between 0.552 inches and 0.572 inches

**Power Dissipation Rating In Watts:** 

10.000 heat sink

**Terminal Width:** 

0.140 inches

**Mounting Hole Size:** 

Between 0.089 inches and 0.099 inches

**Special Features:** 

Resistance values: 0.10 ohms, 5, 620 ohms

**Unpackaged Unit Weight:** 

8.0 grams

**Style Designator:** 

Axial terminal (s)

## NSN 5905-01-501-5963

Inductive Wire Wound Fixed Resistor - Page 2 of 2



## **Test Data Document:**

81349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-prf-39009/1	government specification
-----------------------	--------------------------

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39009 spec.