# NSN 5905-01-501-6870

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-501-6870

### Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

#### **Electrical Resistance:**

121.000 kilohms

#### **Resistance Tolerance In Percent:**

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

#### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+175.0

#### **Inclosure Method:**

Hermetically sealed

#### **Terminal Type:**

Wire lead

### Reliability Indicator:

Established

## Reliability Failure Rate Level In Percent:

1.000

#### Terminal Length:

Between 1.375 inches and 1.625 inches

#### **Body Diameter:**

Between 0.078 inches and 0.140 inches

#### **Body Length:**

Between 0.204 inches and 0.281 inches

#### **Power Dissipation Rating In Watts:**

0.100 free air

### Terminal Width:

Between 0.023 inches and 0.027 inches

#### **Special Features:**

Voltage rating: 200 volts ; resistance values: 10.0 ohms , 2.00 megohms

## Test Data Document:

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-prf-55182/1 government specification

#### Shelf Life:

N/a

Unit Of Measure:

- ---
- Demilitarization:

No

# NSN 5905-01-501-6870

Film Fixed Resistor - Page 2 of 2

Fiig: A001a0 Mil-std (military Standard):

Mil-prf-55182 spec.

