NSN 5905-01-502-3239

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-502-3239 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.437 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** Between 0.614 inches and 0.658 inches **Mounting Bushing Length:** Between 0.614 inches and 0.656 inches **Body Length:** Between 0.821 inches and 0.841 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Terminal Type And Quantity:**

3 turret Shelf Life: N/a **Unit Of Measure:**

NSN 5905-01-502-3239

Precision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0