## NSN 5905-01-504-8644

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-504-8644

**Electrical Resistance:** 39,200 kilohms **Resistance Tolerance In Percent:** -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 **Inclosure Method:** Encased **Terminal Type:** Tab, solder lug **Reactance Characteristic:** Noninductive **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Terminal Length:** Between 0.376 inches and 0.500 inches **Body Length:** Between 1.876 inches and 2.000 inches **Body Width:** Between 0.532 inches and 0.656 inches **Body Height:** Between 0.594 inches and 0.656 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** Between 1.552 inches and 1.572 inches **Power Dissipation Rating In Watts:** 10.000 free air **Terminal Width:** 0.140 inches **Mounting Hole Size:** Between 0.120 inches and 0.130 inches **Unpackaged Unit Weight:** 35.0 grams **Style Designator:** Axial terminal (s) **Test Data Document:** 81349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-prf-39009/2 government specification

## NSN 5905-01-504-8644

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0

Mil-std (military Standard): Mil-prf-39009 spec.