## NSN 5905-01-508-8015

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-508-8015

grand an infrared and grant and an area and an area and an area and area an
Electrical Resistance:
140.000 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
250.0
Inclosure Method:
Encapsulated
Terminal Type:
Threaded stud
Reactance Characteristic:
Noninductive
Reliability Indicator:
Not established
Terminal Length:
Between 1.188 inches and 1.312 inches
Body Length:
Between 3.496 inches and 3.594 inches
Body Width:
Between 1.781 inches and 1.843 inches
Body Height:
Between 1.719 inches and 1.781 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 2.740 inches and 2.760 inches
Power Dissipation Rating In Watts:
75.000 free air
End Application:
Burner, cat
Mounting Hole Size:
Between 0.178 inches and 0.198 inches
Unpackaged Unit Weight:
880.0 grams
Style Designator:
Axial terminal (s)
Test Data Document:
81349-mil-prf-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-prf-18546/2 government specification

Shelf Life:

N/a

## NSN 5905-01-508-8015

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:	
No	
Fiig:	
A001a0	

Mil-std (military Standard):

Mil-prf-18546 spec.

**Unit Of Measure:**