## NSN 5905-01-508-9022

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-508-9022 **Electrical Resistance:** 0.787 ohms **Resistance Tolerance In Percent:** -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 **Inclosure Method:** Encased **Terminal Type:** Tab, solder lug **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: **Body Length:** 1.938 inches **Body Width:** 0.594 inches **Body Height:** 0.625 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.562 inches **Power Dissipation Rating In Watts:** 10.000 free air **End Application:** Consloe wpn I, los angelesclass ssn (688) **Mounting Hole Size:** 0.188 inches **Style Designator:** Axial terminal (s) **Test Data Document:** 81349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-prf-39009/1 government specification Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5905-01-508-9022

Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39009 spec.