# NSN 5905-01-509-0556

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-509-0556

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-25.0/+25.0

### **Electrical Resistance:**

7.230 kilohms

### **Resistance Tolerance In Percent:**

-0.100/+0.100

### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+175.0

### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

Wire lead

### Mil-std-1276 Wire Lead Type Designator:

```
С
```

### **Reliability Indicator:**

Established

## Reliability Failure Rate Level In Percent:

0.010

### **Terminal Length:**

Between 1.375 inches and 1.625 inches

### **Body Diameter:**

Between 0.157 inches and 0.250 inches

### **Body Length:**

Between 0.531 inches and 0.656 inches

### **Power Dissipation Rating In Watts:**

0.250 free air

#### Unpackaged Unit Weight:

0.84 grams

#### Style Designator:

Axial terminal each end

### Test Data Document:

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-prf-55182/5 government specification

## Shelf Life:

N/a

## Unit Of Measure:

# NSN 5905-01-509-0556

Film Fixed Resistor - Page 2 of 2

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.

