NSN 5905-01-509-0948

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-509-0948

Electrical Resistance: 21.000 ohms **Resistance Tolerance In Percent:** -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 **Inclosure Method:** Encased **Terminal Type:** Tab, solder lug **Reactance Characteristic:** Noninductive **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 1.000 **Terminal Length:** Between 0.204 inches and 0.328 inches **Body Length:** Between 0.538 inches and 0.662 inches **Body Width:** Between 0.272 inches and 0.396 inches **Body Height:** Between 0.289 inches and 0.351 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** Between 0.434 inches and 0.454 inches **Power Dissipation Rating In Watts:** 3.000 free air **Terminal Width:** 0.085 inches **Mounting Hole Size:** Between 0.088 inches and 0.098 inches **Unpackaged Unit Weight:** 16.5 grams **Style Designator:** Axial terminal (s) **Test Data Document:** 81349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

81349-mil-prf-39009/2 government specification

Specification Data:

NSN 5905-01-509-0948

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-prf-39009 spec.