NSN 5905-01-510-3620

Section Quantity:

3 tab, solder lug

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-510-3620

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.250 inches
Flat Height:
Between 0.211 inches and 0.221 inches
Body Diameter:
1.094 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
Between 0.762 inches and 1.188 inches
Mounting Bushing Length:
Between 0.360 inches and 0.432 inches
Body Length:
Between 0.468 inches and 0.750 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Terminal Type And Quantity:

NSN 5905-01-510-3620

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Sneit Lite:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0