Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-510-3620

Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.250 inches Flat Height: Between 0.211 inches and 0.221 inches **Body Diameter:** 1.094 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.762 inches and 1.188 inches **Mounting Bushing Length:** Between 0.360 inches and 0.432 inches **Body Length:** Between 0.468 inches and 0.750 inches Shaft Style: Round, flatted Actuator Type: Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear-bottom **Mounting Method:**

Standard bushing

Electrical Resistance Per Section:

100.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0