Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-512-5877

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.500 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.625 inches

#### Mounting Bushing Length:

0.250 inches

#### Body Length:

# 0.453 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

#### Terminal Location:

Rear end

#### **Mounting Method:**

Standard bushing

## **Electrical Resistance Per Section:**

50.0 kilohms single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

## Power Dissipation Rating Per Section In Watts:

1.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

125.0 single section

#### Standard Taper Curve Per Section:

A single section



# Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0