

View Online at <https://aerobasegroup.com/nsn/5905-01-513-7896>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.6250 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.7810 inches

Undercut Width:

0.0570 inches

Body Diameter:

0.8750 inches

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

0.3750 inches

Body Length:

0.8750 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.60 inch-ounces

Maximum Running Torque:

0.060 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.004 inches

Pilot Diameter Runout:

0.002 inches

Shaft Radial Play:

0.002 inches

Fragility Factor:

Rugged

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.10/+0.10 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-140.0/-60.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0