Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-515-0345

# Section Quantity:

10

Body Style:

Cylindrical bushing mounted

### Reliability Indicator:

Not established

### **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.2497 inches

### Shaft Length:

0.500 inches

Mounting Bushing Length:

#### 0.312 inches

Body Length:

### 0.750 inches

Shaft Style:

#### Round

Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

### Maximum Starting Torque:

0.90 inch-ounces

#### Maximum Running Torque:

0.70 inch-ounces

#### Screw Thread Diameter:

0.375 inches

# Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Longitudinally positioned on the circumference

# **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

500.0 ohms 3rd section

# Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

# Fixed Tap Quantity Per Section:

1 all sections



#### **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

### Terminal Type And Quantity:

3 eyelet w/tab

Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

No

#### Fiig:

A002a0