

View Online at <https://aerobasegroup.com/nsn/5905-01-516-5778>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

Between 0.844 inches and 0.906 inches

**Shaft Diameter:**

Between 0.124 inches and 0.126 inches

**Shaft Length:**

Between 0.578 inches and 0.672 inches

**Mounting Bushing Length:**

Between 0.219 inches and 0.297 inches

**Body Length:**

Between 0.625 inches and 0.751 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**End Application:**

Run in consol

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

50.0 ohms single section

**Power Dissipation Rating Per Section In Watts:**

12.5 heat sink single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0