Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-518-1842

Electrical Resistance:

392.000 ohms

Resistance Tolerance In Percent:

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

Inclosure Method:

Encased

Terminal Type:

Tab, solder lug

Reactance Characteristic:

Inductive

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.010

Body Length:

Between 1.876 inches and 2.000 inches

Body Width:

Between 0.376 inches and 0.656 inches

Body Height:

Between 0.594 inches and 0.656 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.522 inches and 1.572 inches

Power Dissipation Rating In Watts:

10.000 free air

End Application:

3ch60sx airframe arr; bl-mh605 knighthawk

Mounting Hole Size:

Between 0.120 inches and 0.130 inches

Criticality Code Justification:

Agav

Style Designator:

Axial terminal (s)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5905-01-518-1842

Inductive Wire Wound Fixed Resistor - Page 2 of 2

Fiig: A001a0

