## NSN 5905-01-518-4560

**Section Quantity:** 

Cylindrical bushing mounted

Between 0.092 inches and 0.096 inches

Reliability Indicator:

Not established First Flat Length:

0.359 inches **Flat Height:** 

**Body Diameter:** 

**Body Style:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-518-4560

0.500 inches
Shaft Diameter:
Between 0.124 inches and 0.126 inches
Shaft Length:
0.420 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.594 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
End Application:
Sof actf
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section

## NSN 5905-01-518-4560

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0