## NSN 5905-01-520-6468

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-520-6468 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** Between 0.124 inches and 0.126 inches **Shaft Length:** 0.412 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.500 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 248.0 **Terminal Location:** Rear-bottom **Mounting Method:** Locking bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 295.0 and 300.0 **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section

**Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Terminal Type And Quantity:** 5 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

## NSN 5905-01-520-6468

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	$\sim$	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A002a0