NSN 5905-01-523-1239

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-523-1239

273.000 kilohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Note established Body Length: -1.986 inches Body Width: -0.630 inches Body Height: -0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: -1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: -0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelt Itie: Na Unit Of Measure: Demilitarization: No Filig: H00100	Electrical Resistance:
Anbient Tempurature In Deg Celsius At Full Rated Power: 25.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: 1.968 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.552 inches Power Dissipation Rating in Watts: 0.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	273.000 kilohms
Ambient Tempurature in Deg Ceisius At Full Rated Power: 25.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: 1.968 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.552 inches Power Dissipation Rating in Watts: 0.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Resistance Tolerance In Percent:
25.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: 1,968 inches Body Width: 0,630 inches Body Height: 0,610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1,562 inches Power Dissipation Rating In Watts: 50,000 heat sink Mounting Hole Size: 0,125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Sheff Life: Na Unit Of Measure: Demilitarization: No Fig:	-1.000 to 1.000
Inclosure Method: Encapsulated Terminal Type: Tab., solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: 1,968 inches Body Width: 0,630 inches Body Height: 0,610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1,562 inches Power Dissipation Rating In Watts: 50,000 heat sink Mounting Hole Size: 0,125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Encapsulated Torminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: 1,968 inches Body Width: 0,630 inches Body Height: 0,640 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1,562 inches Power Dissipation Rating In Watts: 50,000 heat sink Mounting Hole Size: 0,125 inches Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	25.0
Teminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: 1.988 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 0.000 heat sink Mounting Hole Size: 0.125 inches Poecial Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: Via Unit Of Measure: Demilitarization: No Filig:	Inclosure Method:
Tab. solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: 1,968 inches Body Width: 0,630 inches Body Height: 0,610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1,562 inches Power Dissipation Rating In Watts: 0,000 heat sink Mounting Hole Size: 0,125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Encapsulated
Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: 1.968 Inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: Na Unit Of Measure: Demilitarization: No Filig:	Terminal Type:
Inductive Reliability Indicator: Not established Body Length: 1.968 inches Body Wildth: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: Na Unit Of Measure: Demilitarization: No Filg:	Tab, solder lug
Reliability Indicator: Not established Body Length: 1.968 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reactance Characteristic:
Note established Body Length: 1.968 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inductive
Body Length: 1.968 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
1.988 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig:	Body Length:
Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig:	1.968 inches
Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Width:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.630 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Height:
1.562 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.610 inches
Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
50.000 heat sink Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.562 inches
Mounting Hole Size: 0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
0.125 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	50.000 heat sink
Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting Hole Size:
Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.125 inches
Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal (s)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0