## NSN 5905-01-523-1240

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-523-1240

116.000 kilohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: Between 1.781 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.157 inches and 3.010 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: Na Unit Of Measure: Demilitarization: No Filig: A001a0	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: Between 4.469 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Width: Between 1.781 inches and 2.219 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating in Watts: 0.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Azial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	116.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: Between 4.469 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Width: Between 1.781 inches and 1.843 inches Body Height: Between 2.167 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit of Measure: Demilitarization: No Flig:	Resistance Tolerance In Percent:
25.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: Between 4.69 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between 2.157 inches and 3.010 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	-1.000 to 1.000
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: Between 4.469 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Encapsulated Terminal Type: Tab, solder lug Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: Between 4.469 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Height: Between 1.781 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches  Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	25.0
Teminal Type: Tab, solder lug  Reactance Characteristic: Inductive  Reliability Indicator: Not established Body Length: Between 4.469 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Height: Between 2.157 inches and 2.219 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inclosure Method:
Tab, solder lug  Reactance Characteristic: Inductive  Reliability Indicator: Not established Body Length: Between 4.469 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Height: Between 2.157 inches and 2.219 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reactance Characteristic: Inductive Reliability Indicator: Not established Body Length: Between 4.469 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
Inductive Reliability Indicator: Not established Body Length: Between 4.469 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Tab, solder lug
Reliability Indicator: Not established  Body Length: Between 4.469 inches and 4.531 inches  Body Width: Between 1.781 inches and 1.843 inches  Body Height: Between 2.157 inches and 2.219 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches  Power Dissipation Rating In Watts: 50.000 heat sink  Mounting Hole Size: Between 0.178 inches and 0.198 inches  Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Reactance Characteristic:
Note stablished  Body Length:  Between 4.469 inches and 4.531 inches  Body Width:  Between 1.781 inches and 1.843 inches  Body Height:  Between 2.157 inches and 2.219 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  Between 2.990 inches and 3.010 inches  Power Dissipation Rating In Watts:  50.000 heat sink  Mounting Hole Size:  Between 0.178 inches and 0.198 inches  Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Inductive
Bedy Length: Between 4.469 inches and 4.531 inches Body Width: Between 1.781 inches and 1.843 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Between 4.469 inches and 4.531 inches  Body Width:  Between 1.781 inches and 1.843 inches  Body Height:  Between 2.157 inches and 2.219 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  Between 2.990 inches and 3.010 inches  Power Dissipation Rating In Watts:  50.000 heat sink  Mounting Hole Size:  Between 0.178 inches and 0.198 inches  Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:  —  Demilitarization:  No  Fig:	Not established
Between 1.781 inches and 1.843 inches  Body Height:  Between 2.157 inches and 2.219 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  Between 2.990 inches and 3.010 inches  Power Dissipation Rating In Watts: 50.000 heat sink  Mounting Hole Size:  Between 0.178 inches and 0.198 inches  Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:  —  Demilitarization:  No  Fig:	Body Length:
Between 1.781 inches and 1.843 inches  Body Height:  Between 2.157 inches and 2.219 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  Between 2.990 inches and 3.010 inches  Power Dissipation Rating In Watts:  50.000 heat sink  Mounting Hole Size:  Between 0.178 inches and 0.198 inches  Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel  Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:  —  Demilitarization:  No  Fig:	Between 4.469 inches and 4.531 inches
Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 50.000 heat sink Mounting Hole Size: Between 0.178 inches and 0.198 inches Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel Style Designator: Axial terminal (s) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Width:
Between 2.157 inches and 2.219 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  Between 2.990 inches and 3.010 inches  Power Dissipation Rating In Watts: 50.000 heat sink  Mounting Hole Size:  Between 0.178 inches and 0.198 inches  Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel  Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Between 1.781 inches and 1.843 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  Between 2.990 inches and 3.010 inches  Power Dissipation Rating In Watts: 50.000 heat sink  Mounting Hole Size:  Between 0.178 inches and 0.198 inches  Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel  Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Height:
Between 2.990 inches and 3.010 inches  Power Dissipation Rating In Watts:  50.000 heat sink  Mounting Hole Size:  Between 0.178 inches and 0.198 inches  Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel  Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Between 2.157 inches and 2.219 inches
Power Dissipation Rating In Watts: 50.000 heat sink  Mounting Hole Size: Between 0.178 inches and 0.198 inches  Special Features: Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel  Style Designator: Axial terminal (s)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
50.000 heat sink  Mounting Hole Size:  Between 0.178 inches and 0.198 inches  Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel  Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Between 2.990 inches and 3.010 inches
Mounting Hole Size:  Between 0.178 inches and 0.198 inches  Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel  Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Between 0.178 inches and 0.198 inches  Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel  Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	50.000 heat sink
Special Features:  Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel  Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Mounting Hole Size:
Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel  Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Between 0.178 inches and 0.198 inches
Style Designator:  Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Special Features:
Axial terminal (s)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Encapsulant material is silicone molded construction, housing is aluminum with hard anodic coating, end caps are stainless steel
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal (s)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0