NSN 5905-01-523-6554

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-523-6554 **Electrical Resistance:** 68.100 ohms **Resistance Tolerance In Percent:** -0.100/+0.100Ambient Tempurature In Deg Celsius At Full Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 **Inclosure Method:** Encapsulated **Terminal Type:** Wire lead **Reactance Characteristic:** Inductive **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Terminal Length:** 1.500 inches **Body Diameter:** Between 0.063 inches and 0.125 inches **Body Length:** Between 0.375 inches and 0.437 inches **Power Dissipation Rating In Watts:** 2.000 free air **Unpackaged Unit Weight:** 1.0 grams Style Designator: Axial terminal each end **Test Data Document:** 81349-mil-prf-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-prf-39007/8 government specification Shelf Life: N/a **Unit Of Measure:**

Fiig: A001a0

No

Demilitarization:

NSN 5905-01-523-6554

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-39007 spec.