# NSN 5905-01-524-2408

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-524-2408

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0/+50.0

## **Electrical Resistance:**

12.000 kilohms

# **Resistance Tolerance In Percent:**

-0.100/+0.100

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+175.0

# **Inclosure Method:**

Hermetically sealed

### **Terminal Type:**

Wire lead

# Mil-std-1276 Wire Lead Type Designator:

```
С
```

# **Reliability Indicator:**

Established

# Reliability Failure Rate Level In Percent:

0.100

### Body Diameter:

0.188 inches

# Body Length:

0.625 inches

# **Power Dissipation Rating In Watts:**

0.250 free air

# Unpackaged Unit Weight:

0.84 grams

### Style Designator:

Axial terminal each end

### Test Data Document:

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-prf-55182/5 government specification

## Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5905-01-524-2408

Film Fixed Resistor - Page 2 of 2

Fiig: A001a0 Mil-std (military Standard):

Mil-prf-55182 spec.

