## NSN 5905-01-525-4712

Film Fixed Chip Resistor - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5905-01-525-4712
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0 first temp coefficient
Electrical Resistance:
499.000 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+150.0 temp range of first temp coefficient
Inclosure Method:
Uninclosed
Terminal Type:
Terminal type per body style
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.100
Terminal Length:
Between 0.010 inches and 0.020 inches
Body Length:
Between 0.074 inches and 0.086 inches
Body Width:
Between 0.045 inches and 0.055 inches
Body Height:
Between 0.015 inches and 0.033 inches
Power Dissipation Rating In Watts:
0.100 free air
Style Designator:
Termination pad each end
Test Data Document:
81349-mil-prf-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349 - mil-prf-55342/6 government specification
Shelf Life:

No

N/a

**Unit Of Measure:** 

Demilitarization:

## NSN 5905-01-525-4712

Film Fixed Chip Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55342 spec.