## NSN 5905-01-526-2116

-25.0/+25.0

1.370 kilohms

**Electrical Resistance:** 

Film Fixed Chip Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-526-2116

**Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:** 

| Resistance Tolerance In Percent:   |
|--|
| -0.100/+0.100  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 150.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+150.0   |
| Inclosure Method:  |
| Uninclosed   |
| Terminal Type:   |
| Wrap around  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.010  |
| Terminal Length:   |
| 0.5 millimeters  |
| Body Length:   |
| 3.2 millimeters  |
| Body Width:  |
| 1.6 millimeters  |
| Body Height:   |
| Between 0.3 millimeters and 0.8 millimeters  |
| Power Dissipation Rating In Watts:   |
| 0.125 free air   |
| Style Designator:  |
| Termination pad each end   |
| Test Data Document:  |
| 81349-mil-prf-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Specification Data:  |
| 81349-mil-prf-55342/7 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |

## NSN 5905-01-526-2116

Film Fixed Chip Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55342 spec.