NSN 5905-01-526-3114

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-526-3114 **Section Quantity:** 2 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.875 inches **Mounting Slot Width:** 0.031 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.062 inches **Body Width:** 0.500 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted Switch Type: Push-pull **Actuator Type:** Single shaft **Switch Contact Arrangement:** Single pole, double throw, three positions maintained **Center To Center Distance Between Terminals:** 0.100 inches **Mounting Facility Quantity:** 1 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Slot **Features Provided:**

Switch

Electrical Resistance Per Section:

2500.0 ohms all sections

NSN 5905-01-526-3114

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| _ | | | _ | _ | | _ | | |
|--------|--------|--------------|------------|-----------|----------|-----------|----------|------------|
| | Ta Car | nter Distand | a Daturaan | Cantar | Tarminal | A 15 al / | 740.140 | Tarminal. |
| .enter | 100.0 | Her instanc | :e beiweer | ı C.enter | IEMMINAL | Anna | JUITSIME | i erminai: |
| | | | | | | | | |

0.100 inches

Power Dissipation Rating Per Section In Watts:

0.5 heat sink all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0