Film Fixed Chip Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-526-5734

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

#### **Electrical Resistance:**

121.000 ohms

#### **Resistance Tolerance In Percent:**

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

#### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+150.0

#### **Inclosure Method:**

Uninclosed

#### **Terminal Type:**

# Wrap around

Reliability Indicator:

#### Established

**Reliability Failure Rate Level In Percent:** 

0.010

#### **Terminal Length:**

0.020 inches

#### **Body Length:**

0.209 inches

#### Body Width:

0.098 inches

**Body Height:** 

Between 0.015 inches and 0.033 inches

#### **Power Dissipation Rating In Watts:**

0.600 free air

#### Style Designator:

Termination pad each end

#### **Test Data Document:**

81349-mil-prf-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-prf-55342/8 government specification

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# NSN 5905-01-526-5734

Film Fixed Chip Resistor - Page 2 of 2



Fiig: A001a0 Mil-std (military Standard):

Mil-prf-55342 spec.