Film Fixed Chip Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-526-5735

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

# **Electrical Resistance:**

12.000 ohms

# **Resistance Tolerance In Percent:**

-2.000/+2.000

# Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+150.0

#### **Inclosure Method:**

Uninclosed

# **Terminal Type:**

# Wrap around

Reliability Indicator:

# Established

**Reliability Failure Rate Level In Percent:** 

0.010

# **Terminal Length:**

0.015 inches

# **Body Length:**

0.105 inches

#### **Body Width:**

0.100 inches

**Body Height:** 

Between 0.015 inches and 0.033 inches

# **Power Dissipation Rating In Watts:**

0.500 free air

# Style Designator:

Termination pad each end

# **Test Data Document:**

81349-mil-prf-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-prf-55342/10 government specification

# Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:
- No

# NSN 5905-01-526-5735

Film Fixed Chip Resistor - Page 2 of 2



Fiig: A001a0 Mil-std (military Standard):

Mil-prf-55342 spec.