NSN 5905-01-526-5742

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-526-5742

| view Online at https://aerobasegroup.com/nsn/5905-01-526-5742 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -50.0/+50.0 |
| Electrical Resistance: |
| 56.200 kilohms |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 8 |
| Terminal Type: |
| Pin |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.125 inches and 0.150 inches |
| Body Length: |
| Between 0.760 inches and 0.798 inches |
| Body Width: |
| 0.098 inches |
| Body Height: |
| Between 0.177 inches and 0.197 inches |
| Schematic Diagram Designator: |
| Ladder network |
| Power Dissipation Rating In Watts: |
| 0.480 total network |
| Terminal Width: |
| Between 0.013 inches and 0.025 inches |
| Identical Value Resistor Quantity: |
| 4 each resistor |
| Style Designator: |
| Single inline |
| Test Data Document: |
| 81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-83401/8 government specification

NSN 5905-01-526-5742

Film Fixed Resistor Network - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| | |

Mil-std (military Standard):

Shelf Life:

Mil-prf-83401 spec.