NSN 5905-01-527-6673

Film Fixed Resistor - Page 1 of 1

Mil-prf-55182 spec.



View Online at https://aerobasegroup.com/nsn/5905-01-527-6673

Tompurature Coefficient Of Resistance In Dam Box Don Coloius
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-50.0/+50.0 first temp coefficient
Electrical Resistance:
255.000 ohms
Resistance Tolerance In Percent:
-0.100/+0.100
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
175.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+0.0 temp range of first temp coefficient Inclosure Method:
Encapsulated Towns of Towns
Terminal Type:
Wire lead
Reliability Indicator:
Established Polichility Follows Bota Level In Borocott
Reliability Failure Rate Level In Percent:
0.001
Body Diameter:
0.065 inches
Body Length:
0.150 inches
Power Dissipation Rating In Watts:
0.050 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0
Mil-std (military Standard):